

| | Product | Sinopec Xplore 10W-40 4T Motorcycle Oil SN/MA2 | | |
|--|---------|---|--|--|
| | Summary | Product description Sinopec Xplore 10W-40 4T Motorcycle Oil (SN/MA2) is formulated with high- quality semi-synthetic base oils and a multifunctional additive system. It meets the requirements of the Japanese Automobile Standards Organization (JASO), as a JASO MA2 quality product. This multi-grade oil is suitable for four-stroke gasoline motorcycle engines fitted with wet clutches. | | |

Available sizes



Applications

Sinopec Xplore 10W-40 4T Motorcycle Oil (SN/MA2) is suitable for use in:

- Synthetic technology lubricant for high-performance, air or water cooled, four-stroke gasoline engines, where a highest quality oil specification of JASO MA2 is required.
- Fortified with DUAL PROTECHTM technology for enhanced cleanliness and power output.
- Also suitable for gasoline motorcycle engines that requires a lower specification.

Features and benefits

- Protects engine and transmission from start to full power.
- Developed for extended engine and oil life.
- Excellent temperature stability.
- Improves engine power.
- Reinforced engine cleanliness.
- Outstanding loss characteristic with enhanced seal protection.
- Optimum frictional characteristics to prevent clutch slippage.



Typical data

| Sinopec Xplore 10W-40 4T Motorcycle Oil SN/MA2 | | | |
|---|--------|--|--|
| SAE grade | 10W-40 | | |
| Kinematic viscosity, cSt @ 100℃, ASTM D 445 | 14.4 | | |
| CCS, cP @ -25°C, ASTM D5293 | 6710 | | |
| MRV, cP @ -30°C, ASTM D4684 | 25100 | | |
| High-temperature, high-shear viscosity (HTHS), cP $@~150^{\circ}$ C, ASTM D4683 | 4.1 | | |
| Total base number, mg KOH/g, ASTM D 2896 | 7.42 | | |
| Pour point, ℃, ASTM D 97 | -33 | | |
| Flash point (COC), °C, ASTM D 92 | 226 | | |

These data are given as an indication of typical values, not as exact specifications.

Industry and OEM specifications

Sinopec Xplore 10W-40 4T Motorcycle Oil SN/MA2 meets the performance requirements of the following industry specifications:

| API Service Classification | Petrol/Gasoline: SN |
|----------------------------|---------------------|
| ISO | 24254 |
| JASO | T 903 MA2 |

Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Sinopec guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Sinopec cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

Product and environmental safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Safety Data Sheet (SDS) is followed. Please consult the SDS for more detailed advice on handling; SDSs are available from your local distributor. Do not use the product in applications other than those suggested.

As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The SINOPEC trademark is registered and protected.

Issued: March 2022

© Sinopec 2022

Sinopec Xplore 10W-40 4T Motorcycle Oil SN/MA2



The information contained herein is subject to change without notification due to continuing research & development therefore properties may be subject to slight variations.